



Apex Microwave Co. LTD

Web: www.apextech-mw.com E-mail: sales@apextech-mw.com TEL: [+86-28-85555062](tel:+86-28-85555062)

Add: Yuehu Technology Center, Wuhou District, Chengdu, Sichuan, China

Cavity Combiner A6CC758M2690MDL55

Revision record

Date	Version	Author	Revision description	Comment
2024/09/14	V1.1	Lee	Created	/

Electrical specification

Parameter	Specifications					
Frequency range	758-803MHz	869-890MHz	925-960MHz	1805-1880MHz	2110-2170MHz	2620-2690MHz
Center frequency	780.5MHz	879.5MHz	942.5MHz	1842.5MHz	2140MHz	2655MHz
Return loss	≥18dB	≥18dB	≥18dB	≥18dB	≥18dB	≥18dB
Center frequency insertion loss(Normal temp)	≤0.6dB	≤1.0dB	≤0.6dB	≤0.6dB	≤0.6dB	≤0.6dB
Center frequency insertion loss(Full temp)	≤0.65dB	≤1.0dB	≤0.65dB	≤0.65dB	≤0.65dB	≤0.65dB
Insertion loss in bands	≤1.5dB	≤1.7dB	≤1.5dB	≤1.5dB	≤1.5dB	≤1.5dB
Ripple in bands	≤1.0dB	≤1.0dB	≤1.0dB	≤1.0dB	≤1.0dB	≤1.0dB
Rejection at all stop bands	≥50dB	≥55dB	≥50dB	≥50dB	≥50dB	≥50dB
Stop band ranges	703-748MHz & 824-849MHz & 896-915MHz & 1710-1785MHz & 1920-1980MHz & 2500-2570MHz & 2300-2400MHz & 3550-3700MHz					
Input power	≤80W Average handling power at every input port					



Apex Microwave Co. LTD

Web: www.apextech-mw.com E-mail: sales@apextech-mw.com TEL: +86-28-85555062


Add: Yuehu Technology Center, Wuhou District, Chengdu, Sichuan, China

Output power	≤300W Average handling power at COM port
Impedance	50 Ω
Temperature range	-40°C to +85°C

Mechanical specification

Parameter	Specifications
Dimension	L x W x H: 260mm x 181.7mm x 36mm (41.0mm Max)
Input connectors	SMA-Female
COM conector	N-Female
Thread size & Hole callout info	Front: 8-M3 deep 8.0mm Bottom: 4-M4 deep 10.0mm
Weight	≤1.8kg
Finish	Black (Paint spraying)
Notes	Material shall be RoHS 6/6

Outline





Apex Microwave Co. LTD

Web: www.apextech-mw.com

E-mail: sales@apextech-mw.com

TEL: +86-28-85555062

Add: Yuehu Technology Center, Wuhou District, Chengdu, Sichuan, China

Simulation curve

